

M A T E R I A L S A F E T Y D A T A S H E E T

EURO MAX HIGH SOLIDS CLEAR 4.2 VOC

PRODUCT NAME: EURO MAX HIGH SOLIDS CLEAR 4.2 VOC
PRODUCT CODE: AD-575-5L

HMIS CODES: H F R P
2*3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURED FOR : ABI(Autobody Brands International)
A Division of IAMG/International Autobody Marketing Group
ADDRESS : 1505 North Hayden Road, Ste. 111
Scottsdale, AZ 85257
Web Site: www.autobodybrands.com
EMERGENCY PHONE : (800) 424-9300 (24 hrs.)
INFORMATION PHONE : 1-87-REFINISH PREPARER NAME: MSDS Coordinator

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
acrylic polyol/polymer/resin	*****		40%-50%
ACETONE	67-64-1	185 68 F	24.07
ACGIH TLV STEL: 750 ppm			
ACGIH TLV TWA: 500 ppm			
OSHA VPEL TWA: 750 ppm			
OSHA VPEL STEL: 1000 ppm			
* XYLENES	1330-20-7	5.10 68 F	15.79
ACGIH TWA 100 ppm			
ACGIH STEL 150 ppm			
OSHA TWA 100 ppm			
OSHA STEL 150 ppm			
n-BUTYL ACETATE	123-86-4	8.4 68 F	5.13
ACGIH TLV TWA: 150 ppm			
ACGIH TLV STEL: 200 ppm			
OSHA VPEL TWA: 150 ppm			
OSHA VPEL STEL: 200 ppm			
* ETHYL BENZENE	100-41-4	5.1 68 F	3.71
OSHA PEL: 100 ppm TWA			
ACGIH TVL: 100 ppm TWA			
2-(2-hydroxy-3,5-di-(tert)-amylphenyl)benzotriazole	25973-55-1	N/A	0%-10%
STYRENE MONOMER	100-42-5	4.5 68 F	.21
OSHA PEL: 100 ppm			
ACGIH TLV: 20 ppm			
STEL: 40 ppm			

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
N/A

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 133 F - 293 F SPECIFIC GRAVITY (H2O=1): .96
VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than ether
V.O.C. grams/liter: 402.07 V.O.C. lbs./gal.: 3.36
SOLUBILITY IN WATER: Insoluble SOLIDS BY VOLUME: 38.485
APPEARANCE AND ODOR: Clear liquid with organic solvent odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes
PROPOSITION 65 STATEMENT: WARNING! This product contains a chemical or chemicals known to the state of California to cause cancer and/or birth defects or other reproductive harm.

OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
Do not use this product if you have chronic lung or breathing problems.

EMERGENCY AND FIRST AID PROCEDURES
If ingestion, or any type of overexposure or symptoms of overexposure occur during the use of this product, contact a poison control center, emergency room or physician immediately; have material safety data sheet available.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition (sparks, flames, and hot surfaces). Avoid breathing vapors. Ventilate area. Remove with an inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD
Dispose in accordance with state ,federal and local regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Keep containers tightly closed in a cool, dry, well ventilated area away from all possible ignition sources. Store large quantities of material in buildings designed for the storage of flammable liquids.

OTHER PRECAUTIONS
Employees should be trained in safety measures that should be taken when using this product.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION
Avoid breathing vapors or spray mist. Wear a properly fitted respirator approved by NIOSH/MSHA (TC-23c) for use with paints during application and until all vapors are exhausted. In confined areas, or where continuous spray operations are typical, or proper respirator fit is not possible, wear a positive-pressure supplied air respirator (TC-19c). In all cases follow respirator manufactures directions for respirator use. Do not allow anyone without protection into the painting area.

VENTILATION
Provide sufficient ventilation to keep contaminates below applicable OSHA requirements.

PROTECTIVE GLOVES
Neoprene gloves impervious to organic solvents are recommended.

EYE PROTECTION
Use safety eyewear designed to protect against liquid splash.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Impervious coveralls are recommended.

WORK/HYGIENIC PRACTICES
Eye wash and safety showers in the work place are recommended. Wash hands before eating and smoking.

===== SECTION IX - DISCLAIMER =====

The information contained in this material safety data sheet is information from our suppliers and other sources. It is believed to be reliable. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility.